

**NQ TECH GUERRIERO****CARBON FREE HOSE**

APPLICATION	: Recommended for specialist furnace coolant applications in electrical steel industries and other non-conductive applications. Engineered with specially developed carbon free tube and cover that meet service requirements of low leakage current (less than 20 micro A at 6 KV DC).
SPECIFICATION	: SAE 100 R17
TEMPERATURE	: -40°F / +212°F -40°C / +100°C
TUBE	: Gray, modified synthetic rubber
REINFORCEMENT	: High-tenacity synthetic yarn.
COVER	: Green, specially compounded Nitrile.

ID		OD	Working Pressure		Bursting Pressure		Bending Radiusz		Weight	Max Length
MM	INCH	MM	BAR	PSI	MM	INCH	MM	INCH	KG/MTR	MTR
31.00	1.1/4	44..00	17.2	250	69	1000	69	1000	1.20	50
38.00	1.1/2	51.00	17.2	250	69	1000	69	1000	1.35	50
50.00	2	66.00	14	203	56	800	56	800	2.60	40
56.00	2.1/4	77.00	14	203	56	800	56	800	3.50	40
70.00	2.3/4	90.00	14	203	56	800	56	800	7.60	40
75.00	3	96.00	14	203	56	800	56	800	1.90	40
88.00	3.1/2	111.00	14	203	56	800	56	800	2.80	40
100.00	4	124.00	10	145	40	580	40	580	1.90	40