



## NQ TECH GUERRIERO

### PRESSURE WASHER HOSE



- APPLICATION** : For medium pressure cleaning applications with hot water.
- TEMPERATURE** : -40°F/+248°F -40°C / +120°C Intermittent 150°C for pressure washer only
- INNER TUBE** : Synthetic Rubber
- REINFORCEMENT** : One high tensile steel braid
- COVER** : Synthetic rubber with high abrasion, Oz0ne and weather resistance (rubber color and surface finish can be customized as per customer's request)
- FEATURES** : Extreme Abrasion resistant UHMWPE Cove - High temperature (up to 200°C) ~Low temperature (down to -50°C) Fire resistant (MSHA approval)

I.D			R.O.D			O.D		Max w.p		Min b.p		Min b.r	Weight
DASH	DN	INCH	MM	INCH	MM	MM	INCH	BAR	PSI	BAR	PSI	BAR	PSI
-4	6	1/4"	11.2	0.44	13.2	13.2	0.52	280	4000	840	12000	100	0.23
-5	8	5/16"	12.8	0.50	14.8	14.8	0.58	280	4000	840	12000	115	0.27
-6	10	3/8"	15.1	0.59	17.1	17.1	0.67	280	4000	840	12000	130	0.34
-8	12	1/2"	18.1	0.71	20.1	20.1	0.79	280	4000	840	12000	180	0.42

Impulse tested over 1,000,000 cycles without leakage