



SAE 100 R1 AT DIN EN853 1SN (WRAP)

- TUBE : Oil Resistant Synthetic Rubber
- REINFORCEMENT : One High Tensile Steel Wire Braid
- COVER : Abrasion and Weather resistant Synthetic Rubber
- FEATURES : -40°C to +100°C

PRODUCT CODE	HOSE I.D		HOSE OD	MIN B.R	MAX W.P		MIN B.P	
	MM	INCH	MM	MM	BAR	PSI	BAR	PSI
TF-03-R1	4.8-5.2	3/16"	12.1±0.3	90.00	250	3630	1000	14280
TF-04-R1	6.3-6.7	1/4"	13.1±0.3	100.00	225	3270	900	12840
TF-05-R1	7.8-8.2	5/16"	15.0±0.3	114.00	215	3120	850	12280
TF-06-R1	9.4-9.8	3/8"	17.1±0.3	127.00	180	2610	720	10280
TF-08-R1	12.6-13.0	1/2"	20.2±0.3	178.00	160	2320	640	9180
TF-10-R1	16.0-16.4	5/8"	23.6±0.3	200.00	130	1890	520	7420
TF-12-R1	19.0-19.4	3/4"	27.3±0.3	240.00	105	1530	420	6000
TF-16-R1	25.0-25.4	1"	35.0±0.3	300.00	88	1280	350	5020
TF-20-R1	31.7-32.1	1.1/4"	43.6±0.3	419.00	63	920	250	3600
TF-24-R1	38.0-38.4	1.1/2"	50.0±0.3	500.00	50	730	200	2860
TF-32-R1	50.7-51.1	2"	62.7±0.3	630.00	40	580	160	2280