



NQ TECH GUERRIERO



SAE 100 R14 PTFE HOSE

- APPLICATION** : Medium -pressure hydraulic applications including truck, bus, industrial and aerospace. Compatible with air,fuel, lubricants, high-temp oil and sum chemical applications.
- TEMPERATURE** : Meets or exceeds the performance requirements of : SAE 100R14A, FDA 21 CFR 177 , 1500 Specifications
- SPECIFICATIONS** : EN 855 R7 ; SAE 100R7 ; ISO 3949
- INNER TUBE** : Polytetraflourethylene (PTFE) smooth inner tube.
- REINFORCEMENT** : 304 Stainless steel wire briad.
- FEATURES** : 316 stainless steel wire braid-corrugated inner tube-imported PTFE higher temperature range-58°F to 500°F (-50°C to 260°C)

ID			O.D		MAX W.P		MIN B.P		MIN B.R	WEIGHT
DASH	DN	INCH	MM	INCH	BAR	PSI	BAR	PSI	MM	KG/M
-3	3	1/8"	6.2	0.24"	314	4550	1080	15660	45	0076
-4	5	3/16"	7.7	0.3"	240	3480	725	10510	76	0076
-5	6	1/4"	9.2	0.36"	230	3330	680	9860	81	0.13
-6	8	5/16"	10.8	0.43"	194	2810	620	8990	131	0.146
-7	10	3/8"	12.4	0.49"	162	2350	540	7830	182	0.18
-10	12	1/2"	15.9	0.63"	90	1300	360	5220	211	0.22
-12	16	5/8"	19.3	0.76"	80	1180	250	3625	252	0.27
-14	19	3/4"	22.3	0.88"	70	1010	223	3230	300	0.38
-16	222	7/8"	25.8	1.02"	60	870	210	3045	421	0.43
-16	25	1"	29.5	1.16"	50	720	195	2820	485	0.48