



## NQ TECH GUERRIERO



### SAE 100 R15 – ISO 3862 R15

- APPLICATION** : Designed specifically to handle severe high pressure applications where pressure or constant hydrostatic loads are present.
- SPECIFICATION** : SAE 100 R15 - ISO 3862 R15
- TEMPERATURE** : -40°F / +250°F -40°C / +121°C
- TUBE** : Oil resistant synthetic rubber
- REINFORCEMENT** : Four high tensile steel spirals (DN10~25), Six high tensile steel spirals (DN31~38)
- COVER** : Synthetic rubber with high abrasion, ozone and weather resistance, Fire resistant with MSHA approval (rubber color and surface finish can be customized as per customer's request)
- FEATURES** : Extreme Abrasion resistant UHMWPE Cover - High temperature (up to 100°C) - Low temperature (down to -50°C)

I.D		R.O.D		O.D		Max w.p		Min b.r		Min b.r	Weight	Constr.	
DASH	DN	INCH	MM	INCH	MM	INCH	BAR	PSI	BAR	PSI	MM	KG/M	
-6	10	3/8"	17.5	0.69	21.2	0.83	420	6090	1680	24360	150	0.76	4S
-8	12	1/2"	20.3	0.80	24.4	0.96	420	6090	1680	24360	200	1.02	
-12	19	3/4"	28.2	1.11	32.0	1.26	420	6090	1680	24360	265	1.65	
-16	25	1"	35.1	1.38	38.4	1.51	420	6090	1680	24360	330	2.29	
-20	31	1-1/4"	46.3	1.82	49.3	1.94	420	6090	1680	24360	445	3.97	6S
-24	38	1-1/2"	53.7	2.11	57.3	2.26	420	6090	1680	24360	530	4.72	