



SAE-100-R2AT-DIN-EN853-2SN-(SMOOTH)

- TUBE : Oil Resistant Synthetic Rubber
- REINFORCEMENT : Two High Tensile Steel Wire Braid
- COVER : Abrasion and Weather resistant Synthetic Rubber
- FEATURES : -40°C to +100°C

PRODUCT CODE	HOSE I.D		HOSE OD	MIN B.R	MAX W.P		MIN B.P	
	MM	INCH	MM	MM	BAR	PSI	BAR	PSI
TFS-03-R2	4.8-5.2	3/16"	13.4±0.3	90.00	414	6000	1650	23720
TFS-04-R2	6.3-6.7	1/4"	14.8±0.3	100.00	400	5800	1600	22840
TFS-05-R2	7.8-8.2	5/16"	16.7±0.3	114.00	360	5250	1400	20000
TFS-06-R2	9.4-9.8	3/8"	18.7±0.3	127.00	331	4800	1320	18840
TFS-08-R2	12.6-13.0	1/2"	21.9±0.3	178.00	276	4000	1100	15720
TFS-10-R2	16.0-16.4	5/8"	25.4±0.3	200.00	250	3630	1000	14280
TFS-12-R2	19.0-19.4	3/4"	29.0±0.3	240.00	215	3120	850	12280
TFS-16-R2	25.0-25.4	1"	36.7±0.3	300.00	165	2400	650	9420
TFS-20-R2	31.7-32.1	1.1/4"	45.6±0.3	419.00	125	1820	500	7140
TFS-24-R2	38.0-38.4	1.1/2"	52.0±0.3	500.00	90	1310	360	5140
TFS-32-R2	50.7-51.1	2"	64.7±0.3	630.00	80	1160	320	4560