



## SAE-100-R5C-HOSES

- TUBE : Oil Resistant Synthetic Rubber
- REINFORCEMENT : One High Tensile Steel Wire Braid
- COVER : Abrasion and Weather resistant Synthetic Rubber
- FEATURES : -40°C to +100°C

STANDARD	SIZE	I.D	O.D	WORKING PRESSURE			BURSTING PRESSURE		
		MM	MM	MPA	BAR	PSI	MPA	BAR	PSI
RS C	3/16"	4.8	13.2	20.7	207	3000	82.8	828	12000
	1/4"	6.3	14.8	20.7	207	3000	82.8	828	12000
	5/16"	8	17.2	15.5	155	2250	62	620	9000
	13/32"	10.4	19.5	13.8	138	2000	55.2	552	8000
	1/2"	12.7	23.4	12.1	121	1755	48.3	483	7020
	5/8"	16	27.4	10.3	103	1495	41.4	414	5980
	7/8"	22.2	31.4	5.5	55	800	22.1	221	3200
	1 1/8"	28.6±0.3	38.1±0.3	4.3	43	625	17.2	172	2500
	1 3/8"	34.9	44.5	3.4	34	500	13.8	138	2000
	1-13/16"	46	56.4	2.4	24	350	9.7	97	1400
	2-3/8"	60.3	73	2.4	24	350	9.7	97	1400
	3"	76.2	90.5	1.4	14	200	5.5	55	800