



## NQ TECH GUERRIERO

### SAE 100 R5C HOSES



- APPLICATION : For medium pressure hydraulic lines.
- SPECIFICATION : SAE 100 R5C HOSES
- TEMPERATURE : -40°C to +100°C
- TUBE : Black, Oil Resistant NBR TUBE
- REINFORCEMENT : Single braided high tensile steel wire over one braid of yarn.
- COVER : Oil Resistant Rubber Impregnated COVER

I.D		O.D	Working pressure		Bursting pressure		Bending radius	
MM	INCH	MM	BAR	PSI	BAR	PSI	MM	INCH
4.80	3/16	13.20	210	3045	840	12180	76	3.00
6.40	1/4	14.80	210	3045	840	12180	86	3.40
7.90	5/16	17.20	157	2277	628	9106	101	4.00
10.30	13/32	19.50	140	2030	560	8120	117	4.60
12.70	1/2	23.50	122	1769	488	7076	140	5.50
15.90	5/8	27.40	105	1522	420	6090	165	6.50
22.20	7/8	31.40	56	812	224	3248	188	7.40
28.90	1.1/8	38.10	43	624	172	2494	229	9.00
34.90	1.3/8	44.50	35	508	140	2030	267	10.50
46.00	1.12/16	58.90	24	348	96	1395	338	13.3