



SAE-100-R6-DIN-EN854

- TUBE : Oil Resistant Synthetic Rubber
- REINFORCEMENT : One High Tensile fiber Braid
- COVER : Abrasion and Weather resistant Synthetic Rubber
- FEATURES : -40°C to +100°C

STANDARD	SIZE	I.D	O.D	WORKING PRESSURE			BURSTING PRESSURE		
	MM	MM	MM	MPA	BAR	PSI	MPA	BAR	PSI
RS	3/16"	4.8-5.4	10.9-11.9	3.5	35	510	14	140	2040
	1/4"	6.1-6.9	12.5-13.5	2.8	28	410	11.2	112	1640
	5/16"	7.7-8.4	14.1-15.1	2.8	28	410	11.2	112	1640
	3/8"	9.5-10.3	15.7-16.7	2.8	28	410	11.2	112	1640
	1/2"	12.6-13.4	19.4-20.4	2.8	28	410	11.2	112	1640
	5/8"	15.8-16.6	22.8-23.8	2.4	24	350	9.6	96	1400
	3/4"	18.8-19.8	26.4-27.4	2.1	21	300	8.4	84	1200
	7/8"	21.8-22.8	29.7-30.7	2.0	20	300	8.4	84	1200
	1"	24.8-26.0	33.5-34.5	2.0	20	290	8.0	80	1160
	1-1/8"	28.6-29.8	37.4-38.6	2.0	20	290	8.0	80	1160
	1-1/4"	28.6-29.8	43.0-45	1.8	18	290	8.0	80	1160
	1-3/8"	34.6-35.8	46-48	1.5	15	260	7.2	72	1040
	1-1/2"	37.6-38.8	50.0-52.0	1.5	15	220	6.0	60	880
	1-3/4"	44.6-45.8	55.0-57.0	1.5	15	220	6.0	60	880
	2"	50.6-51.8	64.0-66.0	1.5	15	220	6.0	60	880
2-1/2"	63.6-65.8	78-80	1.0	10	220	6.0	60	880	
3"	75.4-76.8	90.5-92.5			150	4.0	40	600	