



NQ **NQ TECH GUERRIERO**

SAE 100 R6 DIN EN854



- APPLICATION** : Low Pressure Hydraulic Oils, Fuel, Lubricating Oil, Anti-Freeze Solution and Water
- SPECIFICATION** : SAE 100 R6-EN854 R6/1TE - ISO 4079-1R6/1TE
- TEMPERATURE** : -40°C to 100°(Intermittent Use upto 110°C)
- TUBE** : Black Oil Resistant Synthetic Rubber Compound
- REINFORCEMENT** : One Braid of Suitable Textile Yarn.
- COVER** : Synthetic Rubber Compound with Abrasion, Ozone and weather Resistant.
- FEATURES** : Robust- High Abrasion Resistant Cover

I.D		Normal bore		Mean outer Cover Dia-meter	Max w.p		Min b.p.		Min b.r	
DASH	DN	INCH	MM	MM	BAR	PSI	BAR	PSI	MM	INCH
-3	5	3/16"	4.8	11.1	35	500	140	2000	51	2.0"
-4	6	1/4"	6.4	12.7	28	400	110	1600	64	2.5"
-5	8	5/16"	7.9	14.3	28	400	110	1600	76	3.0"
-6	10	3/8"	9.5	15.9	28	400	110	1600	76	3.0"
-8	12	1/2"	12.7	19.8	28	400	110	1600	102	4.0"
-10	16	5/8"	15.9	22.8	24	350	96	1400	127	5.0"
-12	20	3/4"	19.0	27.5	21	300	83	1200	152	6.0"
-14	22	7/8"*	22.0*	31.2	21	300	83	1200	152	6.0"
-16	25	1"*	25.4*	30.0	13	190	82	760	230	9.0"