



NQ TECH GUERRIERO



STEAM HOSE

- APPLICATION** : Using in petrochemical industry, shipyard for transferring Saturated and superheated steam.
- TEMPERATURE** : -40°C / +210°C (-40°F / +410°F) intermittent 0 232°C (450°F)
- INNER TUBE** : Black EPDM
- REINFORCEMENT** : Two high tensile steel braids.
- COVER** : Red EPDM perforated rubber with abrasion and ozone resistant

I.D			O.D		Max w.p		Min b.P		Min b.r	Weight
DASH	DN	INCH	MM	INCH	BAR	PSI	BAR	PSI	MM	KG/M
-8	12	1/2"	23	0.98	18	270	180	2700	130	0.42
-10	16	5/8"	26	1.02	18	270	180	2700	160	0.46
-12	19	3/4"	31	1.26	18	270	180	2700	190	0.77
-16	25	1"	38	1.50	18	270	180	2700	250	0.90
-20	32	1 1/4"	46	1.81	18	270	180	2700	320	1.27
-24	38	1 1/2"	52	2.05	18	270	180	2700	380	1.37
-32	51	2"	67	2.64	18	270	180	2700	510	2.05
-40	63	2 1/2"	81	3.19	18	270	180	2700	630	2.96
-48	76	3"	94	3.70	18	270	180	2700	760	3.72

Impulse tested over 1,000,000 cycles without leakage