



NQ TECH GUERRIERO



THERMOPLASTIC HOSE (2 WIRE)

- APPLICATION** : Medium pressure thermoplastic hose with a perforated cover. Compatible with petroleum- water and synthetic. based fluid for mobile equipment, lube lines, blowout preventers, hydraulic lifts and construction Machinery
- TEMPERATURE** : For hydraulic fluids -40°F /+199°F -40°C per +93°C. For water based fluids and air Max +65°C (+149°F)
- INNER TUBE** : Hydraulic oils, air and water based fluids resistant PA
- REINFORCEMENT** : 2 high tensile steel braid.
- COVER** : Oil, abrasion and weather resistant polyurethane.
- FEATURES** : Twin hoses- Pin- pricked

ID			O.D	MAX W.P		MIN B.P		MIN B.R	WEIGHT
DASH	DN	INCH	MM	BAR	PSI	BAR	PSI	MM	KG/M
-4	6	1/4"	13.2	450	6525	1800	25920	40	0.26
-5	8	5/16"	15.2	400	5800	1600	23200	50	0.32
-6	10	3/8"	17.5	380	5510	1520	22040	80	0.38
-8	12	1/2"	21.5	300	4350	1200	17400	90	0.48
-10	16	5/8"	24.5	180	2610	720	10440	100	0.61
-12	19	3/4"	28	160	2320	640	9280	130	0.77
-16	25	1"	35	120	1740	480	6960	150	0.92